



## Konica Minolta Bizhub C224e

### Key Features:

- Konica Minolta Bizhub C224e Speed A4/A3: 22/14 ppm in colour and black & white
- Konica Minolta Bizhub C224e Paper formats: A6-SRA3, custom formats and banner format up to 1.2 metres length
- Konica Minolta Bizhub C224e 9 inch colour touch panel with multi-touch support
- Konica Minolta Bizhub C224e Dual-scan document feeder scans both sides of double-sided originals in one run at a speed of 160 ipm
- Konica Minolta Bizhub C224e Modular finishing and paper tray options for customised configurations

[Read More](#)

**SKU:** C224e

**Price:** 1,650,000.00 Kz C/IVA

**Categories:** [Photocopiers](#)

### Product Description

[Konica Minolta Bizhub C224e Brochure](#)

## Konica Minolta Bizhub C224e Specifications:

**Operating Systems:** Windows 8, Windows 7, Windows Vista, Windows XP, Windows 2000, Mac OS, Linux, Citrix Ready

### Copier Specifications

**Copying process** Electrostatic laser copy, tandem, indirect

**Toner system** Simitri HD® polymerised toner

**Copy/print speed  
A4 mono (cpm)** 22

<b>Copy/print speed A4 colour (cpm)</b>	22
<b>Copy/print speed A3 mono (cpm)</b>	14
<b>Copy/print speed A3 colour (cpm)</b>	14
<b>Autoduplex speed A4 mono (cpm)</b>	22
<b>Autoduplex speed A4 colour (cpm)</b>	22
<b>1st Copy/print time mono (sec)</b>	6.9
<b>1st Copy/print time colour (sec)</b>	8.3
<b>Warm-up time (sec)</b>	Approx. 20 * * Warm up time may vary depending on the operating environment and usage
<b>Copy resolution (dpi)</b>	600 x 600
<b>Gradations</b>	256 gradations
<b>Multi-copy</b>	1-9,999
<b>Original format</b>	A5-A3
<b>Magnification</b>	25-400% in 0.1% steps; auto-zooming
<b>Copy functions</b>	Chapter; cover and page insertion; proof copy (print and screen); adjustment test print; digital art functions; job setting memory; poster mode; image repeat; overlay (optional); stamping; copy protection

### Printer Specifications

<b>Print resolution (dpi)</b>	1,800 x 600 1,200 x 1,200
<b>Controller CPU Speed</b>	800 MHz
<b>Page description language</b>	PCL6 (XL 3.0) PCL 5c PostScript 3 (CPSI 3016) XPS

**Operating systems** Windows XP (32/64) Windows VISTA (32/64) Windows 7 (32/64) Windows 8 (32/64) Windows Server 2003 (32/64) Windows Server 2008 (32/64) Windows Server 2008 R2 (64) Windows Server 2012 (64) Macintosh OS X 10.x Unix, Linux, Citrix

**Printer fonts** 80 PCL Latin; 137 PostScript 3 Emulation Latin

**Print functions** Direct print of PCL, PS, TIFF, XPS, PDF, encrypted PDF files and OOXML (DOCX, XLSX, PPTX); mixmedia and mixplex; "Easy Set" job programming; overlay; watermark; copy protection; carbon copy print

### Scanner Specifications

**Scan speed colour (opm)** Up to 160 ipm (with optional DF-701)

**Scan Speed mono (opm)** Up to 160 ipm (with optional DF-701)

**Scan resolution (dpi)** Max.: 600 x 600

**Scan modes** Scan-to-eMail (Scan-to-Me) Scan-to-SMB (Scan-to-Home) Scan-to-FTP Scan-to-Box Scan-to-USB Scan-to-WebDAV Scan-to-DPWS Network TWAIN scan JPEG; TIFF; PDF; PDF/A 1a and 1b (optional); compact PDF; encrypted PDF;

**File formats** searchable PDF (optional); XPS; compact XPS; PPTX; searchable PPTX (optional); searchable DOCX/XLSX (optional)

**Scan destinations** 2,100 (single + group); LDAP support

**Scan functions** Annotation (text/time/date) for PDF; up to 400 job programs; real-time scan preview

### Fax Specifications

**Fax standard** Super G3 (optional)

**Fax transmission** Analogue i-Fax Colour i-Fax (RFC3949-C) IP-Fax

**Fax resolution (dpi)** Max.: 600 x 600 (ultra-fine)

**Fax compression** MH; MR; MMR; JBIG

**Fax modem (Kbps)** Up to 33.6 Kbps

**Fax destinations** 2,100 (single + group)

**Fax functions** Polling; time shift; PC-Fax; receipt to confidential box; Receipt to e-mail/FTP/SMB; up to 400 job programs

**User box specification**

<b>Max. storable documents</b>	Up to 3,000 documents or 10,000 pages
<b>Type of user boxes</b>	Public Personal (with password or authentication) Group (with authentication)
<b>Type of system boxes</b>	Secure print Encrypted PDF print Fax receipt Fax polling
<b>User box functionality</b>	Reprint; combination Download Sending (e-mail/FTP/SMB and Fax) Copy box to box

**System Specifications**

<b>System memory standard (MB)</b>	2,048 (standard)
<b>System hard disc standard (GB)</b>	250 (standard)
<b>Network protocols</b>	TCP/IP (IPv4 / IPv6); IPX/SPX; NetBEUI; AppleTalk (EtherTalk); SMB; LPD; IPP; SNMP; HTTP
<b>Frame types</b>	Ethernet 802.2; Ethernet 802.3; Ethernet II; Ethernet SNAP
<b>Automatic document feeder</b>	Up to 100 originals; A6-A3; 35-163 gsm RADF or Dualscan ADF available
<b>Paper size</b>	A6-SRA3, customised paper sizes; banner paper max. 1,200 x 297 mm
<b>Printable paper weight (g/m<sup>2</sup>)</b>	52-300 gsm
<b>Paper input capacity (sheets)</b>	Standard: 1,150 Max.: 3,650 sheets
<b>Paper trays standard</b>	Tray 1: 500 sheets, A5-A3, 52-256 gsm Tray 2: 500 sheets, A5-SRA3, 52-256 gsm Manual Bypass: 150 sheets, A6-SRA3, custom sizes, banner, 60-300 gsm
<b>Paper trays optional</b>	Tray 3: 500 sheets, A5-A3, 52-256 gsm Tray 3 + 4: 2x 500 sheets, A5-A3, 52-256 gsm Large Capacity Cabinet: 2,500 sheets, A4, 52-256 gsm
<b>Automatic duplexing</b>	A5-SRA3; 52-256 gsm
<b>Finishing modes (optional)</b>	Offset; group; sort; staple; punch; post insertion; centre-fold; letter fold; booklet
<b>Output capacity (w. finisher)</b>	Max.: 3,300 sheets

<b>Output capacity (w/o finisher)</b>	Max.: 250 sheets
<b>Stapling</b>	50 sheets or 48 sheets + 2 cover sheets (up to 209 gsm)
<b>Stapling output capacity</b>	Max. 1,000 sheets
<b>Letter fold</b>	Up to 3 sheets
<b>Letter fold capacity</b>	Max.: 30 sheets (tray); unlimited
<b>Booklet</b>	Max.: 20 sheets or 19 sheets + 1 cover sheet (up to 209 gsm)
<b>Booklet output capacity</b>	Max.: 100 sheets (tray); unlimited
<b>Copy/print volume recommended (monthly)</b>	13,000 pages
<b>Copy/print volume max. (monthly)</b>	80,000 pages
<b>Toner lifetime Black</b>	27,000
<b>Toner lifetime CMY</b>	25,000
<b>Developer lifetime Black</b>	600,000
<b>Developer lifetime CMY</b>	600,000
<b>Drum lifetime Black</b>	70,000
<b>Drum lifetime CMY</b>	55,000
<b>Power consumption</b>	220-240 V / 50/60 Hz Less than 1.5 kW (system)
<b>System dimensions (WxDxH, mm)</b>	615 x 685 x 779 mm (excl. ADF and lower paper tray unit)
<b>System weight (kg)</b>	Approx. 85

## System Features

<b>Security</b>	ISO 15408 EAL3 (in evaluation); IEEE 2600.1 compliant; IP filtering and port blocking; SSL2; SSL3 and TLS1.0 network communication; IPsec support; IEEE 802.1x support; user authentication; Authentication log; secure print; Hard disc overwrite (8 standard types); Hard disc data encryption (AES 128); Memory data auto deletion; Confidential fax receipt; Print user data encryption; copy protection (Copy Guard, Password Copy) optional
<b>Accounting</b>	Up to 1,000 user accounts; Active Directory support (user name + password + e-mail + smb folder) User function access definition Biometric authentication (finger vein scanner) optional ID card authentication (ID card reader) optional
<b>Software</b>	PageScope Net Care Device Manager PageScope Data Administrator PageScope Box Operator PageScope Direct Print Print Status Notifier Driver Packaging Utility Log Management Utility