



Konica Minolta Bizhub C284e

Key Features

- Konica Minolta Bizhub C284e Speed A4/A3: 28/14 ppm in colour and black & white
- Konica Minolta Bizhub C284e Paper formats: A6-SRA3, custom formats and banner format up to 1.2 metres length
- Konica Minolta Bizhub C284e 9 inch colour touch panel with multi-touch support
- Konica Minolta Bizhub C284e Dual-scan document feeder scans both sides of double-sided originals in one run at a speed of 160 ipm
- Konica Minolta Bizhub C284e Modular finishing and paper tray options for customised configurations

[Read More](#)

SKU: C284e

Price: 1,750,000.00 Kz C/IVA

Categories: [Photocopiers](#)

Product Description

[Konica Minolta bizhub C284e Brochure](#)

Konica Minolta Bizhub C284e Specifications:

Operating Systems: Windows 8, Windows 7, Windows Vista, Windows XP, Windows 2000, Mac OS, Linux, Citrix Ready

Copier Specifications

Copying process Electrostatic laser copy, tandem, indirect

Toner system Simitri HD® polymerised toner

Copy/print speed A4 mono (cpm)	28
Copy/print speed A4 colour (cpm)	28
Copy/print speed A3 mono (cpm)	14
Copy/print speed A3 colour (cpm)	14
Autoduplex speed A4 mono (cpm)	28
Autoduplex speed A4 colour (cpm)	28
1st Copy/print time mono (sec)	5.9
1st Copy/print time colour (sec)	7.7
Warm-up time (sec)	Approx. 20 * * Warm up time may vary depending on the operating environment and usage
Copy resolution (dpi)	600 x 600
Gradations	256 gradations
Multi-copy	1-9,999
Original format	A5-A3
Magnification	25-400% in 0.1% steps; auto-zooming
Copy functions	Chapter; cover and page insertion; proof copy (print and screen); adjustment test print; digital art functions; job setting memory; poster mode; image repeat; overlay (optional); stamping; copy protection

Printer Specifications

Print resolution (dpi)	1,800 x 600 1,200 x 1,200
Controller CPU Speed	800 MHz
Page description language	PCL6 (XL 3.0) PCL 5c PostScript 3 (CPSI 3016) XPS

Operating systems Windows XP (32/64) Windows VISTA (32/64) Windows 7 (32/64) Windows 8 (32/64) Windows Server 2003 (32/64) Windows Server 2008 (32/64) Windows Server 2008 R2 (64) Windows Server 2012 (64) Macintosh OS X 10.x Unix, Linux, Citrix

Printer fonts 80 PCL Latin; 137 PostScript 3 Emulation Latin

Print functions Direct print of PCL, PS, TIFF, XPS, PDF, encrypted PDF files and OOXML (DOCX, XLSX, PPTX); mixmedia and mixplex; "Easy Set" job programming; overlay; watermark; copy protection; carbon copy print

Scanner Specifications

Scan speed colour (opm) Up to 160 ipm (with optional DF-701)

Scan Speed mono (opm) Up to 160 ipm (with optional DF-701)

Scan resolution (dpi) Max.: 600 x 600

Scan modes Scan-to-eMail (Scan-to-Me) Scan-to-SMB (Scan-to-Home) Scan-to-FTP Scan-to-Box Scan-to-USB Scan-to-WebDAV Scan-to-DPWS Network TWAIN scan JPEG; TIFF; PDF; PDF/A 1a and 1b (optional); compact PDF; encrypted PDF;

File formats searchable PDF (optional); XPS; compact XPS; PPTX; searchable PPTX (optional); searchable DOCX/XLSX (optional)

Scan destinations 2,100 (single + group); LDAP support

Scan functions Annotation (text/time/date) for PDF; up to 400 job programs; real-time scan preview

Fax Specifications

Fax standard Super G3 (optional)

Fax transmission Analogue i-Fax Colour i-Fax (RFC3949-C) IP-Fax

Fax resolution (dpi) Max.: 600 x 600 (ultra-fine)

Fax compression MH; MR; MMR; JBIG

Fax modem (Kbps) Up to 33.6 Kbps

Fax destinations 2,100 (single + group)

Fax functions Polling; time shift; PC-Fax; receipt to confidential box; Receipt to e-mail/FTP/SMB; up to 400 job programs

User box specification

Max. storable documents	Up to 3,000 documents or 10,000 pages
Type of user boxes	Public Personal (with password or authentication) Group (with authentication)
Type of system boxes	Secure print Encrypted PDF print Fax receipt Fax polling
User box functionality	Reprint; combination Download Sending (e-mail/FTP/SMB and Fax) Copy box to box

System Specifications

System memory standard (MB)	2,048 (standard)
System hard disc standard (GB)	250 (standard)
Network protocols	TCP/IP (IPv4 / IPv6); IPX/SPX; NetBEUI; AppleTalk (EtherTalk); SMB; LPD; IPP; SNMP; HTTP
Frame types	Ethernet 802.2; Ethernet 802.3; Ethernet II; Ethernet SNAP
Automatic document feeder	Up to 100 originals; A6-A3; 35-163 gsm RADF or Dualscan ADF available
Paper size	A6-SRA3, customised paper sizes; banner paper max. 1,200 x 297 mm
Printable paper weight (g/m²)	52-300 gsm
Paper input capacity (sheets)	Standard: 1,150 Max.: 3,650 sheets
Paper trays standard	Tray 1: 500 sheets, A5-A3, 52-256 gsm Tray 2: 500 sheets, A5-SRA3, 52-256 gsm Manual Bypass: 150 sheets, A6-SRA3, custom sizes, banner, 60-300 gsm
Paper trays optional	Tray 3: 500 sheets, A5-A3, 52-256 gsm Tray 3 + 4: 2x 500 sheets, A5-A3, 52-256 gsm Large Capacity Cabinet: 2,500 sheets, A4, 52-256 gsm
Automatic duplexing	A5-SRA3; 52-256 gsm
Finishing modes (optional)	Offset; group; sort; staple; punch; post insertion; centre-fold; letter fold; booklet
Output capacity (w. finisher)	Max.: 3,300 sheets

Output capacity (w/o finisher)	Max.: 250 sheets
Stapling	50 sheets or 48 sheets + 2 cover sheets (up to 209 gsm)
Stapling output capacity	Max. 1,000 sheets
Letter fold	Up to 3 sheets
Letter fold capacity	Max.: 30 sheets (tray); unlimited
Booklet	Max.: 20 sheets or 19 sheets + 1 cover sheet (up to 209 gsm)
Booklet output capacity	Max.: 100 sheets (tray); unlimited
Copy/print volume recommended (monthly)	16,000 pages
Copy/print volume max. (monthly)	100,000 pages
Toner lifetime Black	27,000
Toner lifetime CMY	25,000
Developer lifetime Black	600,000
Developer lifetime CMY	600,000
Drum lifetime Black	120,000
Drum lifetime CMY	75,000
Power consumption	220-240 V / 50/60 Hz Less than 1.5 kW (system)
System dimensions (WxDxH, mm)	615 x 685 x 779 mm (excl. ADF and lower paper tray unit)
System weight (kg)	Approx. 85

System Features

Security	ISO 15408 EAL3 (in evaluation); IEEE 2600.1 compliant; IP filtering and port blocking; SSL2; SSL3 and TSL1.0 network communication; IPsec support; IEEE 802.1x support; user authentication; Authentication log; secure print; Hard disc overwrite (8 standard types); Hard disc data encryption (AES 128); Memory data auto deletion; Confidential fax receipt; Print user data encryption; copy protection (Copy Guard, Password Copy) optional
Accounting	Up to 1,000 user accounts; Active Directory support (user name + password + e-mail + smb folder) User function access definition Biometric authentication (finger vein scanner) optional ID card authentication (ID card reader) optional
Software	PageScope Net Care Device Manager PageScope Data Administrator PageScope Box Operator PageScope Direct Print Print Status Notifier Driver Packaging Utility Log Management Utility